

	PRODUCT SPECIFICATION	Cod.F65S
		Rev.1/06
		10/01/2006

NAME	65 STADIUM PRO
PRODUCTION PROCESS	Tufting cut pile 3/4" ZIG ZAG
SPORTS APPLICATIONS	Soccer

FIBRE SPECIFICATIONS

COLOURS	Field Green	Tolerances
COMPOSITION OF YARN	Polyethylene 100% lubricated, not abrasive	
DTEX	11.000 Dtex	+/- 4%
STRUCTURE	Monotape fibrillated	
THICKNESS	100 µ	+/- 5%
PILE HEIGHT	63 mm	+/- 5%
TOTAL LENGHT	135 mm	+/- 5%
STITCHES / m²	9.000	+/- 5%
PILE WEIGHT (gr./m²)	1.335 gr.	+/- 5%

BACKING SPECIFICATIONS

PRIMARY BACKING	Ordito: Polipropilene Trama: Poliestere + TNT in Poliestere	stabilizzato ai raggi UV	Tolerances
WEIGHT (gr./m²)	215 gr		+/- 3%
SECONDARY BACKING	Latex Compound XSBR		
WEIGHT (gr./m²)	1.150 gr		+/- 5%

CARATTERISTICHE TAPPETO

TOTAL WEIGHT (gr./m ²)	2.700 gr	Tolerances +/- 5%
ROLL WIDTH	4,05 – 5,05 lm	+/- 0,5%
ROLL LENGHT	On request	+/- 4%
PERMEABILITY	1.000 l/h	+/- 4%

INFILL RECOMMENDED

Siliceous Sand	15 Kg/Sqm
SBR Rubber	15 Kg/Sqm