


FIELD *turf*
FIELD *turf* **EUROPE**
PRODUCT SPECIFICATIONS – EUROPEAN PRODUCTION – METRIC UNITS
PRODUCT NAME – FIELDTURF 70

PROPERTIES	UNITS	STANDARD
Pile Yarn Type	Polyethylene, UV Stabilized	ISO 2060
UV Performance	>80% retained tensile strength after 3000 hours	ISO 4892-2
Linear Density	8890 dTex	BS4611
Yarn Thickness	100 Microns	
Yarn Width	10 mm	
Number of Tufts	8745 M ²	ISO 1763
Yarn Breaking Strength	210 ± 5% N	BS4611
Yarn Maximum Elongation	45 %	BS4611
Vicat Softening Point	120 Degrees C	ISO 306/a
Pile Height	70 mm	
Pile Weight	1245 g/m ²	ISO 2459
Primary Backing Weight	215 g/m ²	ISO 13934-1
Secondary Backing Weight	900 g/m ²	
Total Carpet Weight (without infill)	2360 g/m ²	DIN 53854
Stitch Gauge	¾ Inch	
Tuft withdrawal force (without infill)	>3 daN	ISO 4919
Primary Backing Tensile Strength (weft)	1005 N per 5cm	ISO 13934-1
Primary Backing Tensile Strength (warp)	595 N per 5cm	ISO 13934
Pill Burn Test	T2	NEN 1775
Permeability	>180 mm/hour	EN 12616

INFILL

Specially graded silica sand as per FieldTurf Specifications
Specially grades cryogenic SBR as per FieldTurf Specifications


MANUFACTURED ROLLS

Width (Useable)	4 Meters
Length	Up to 100 Meters
Line Colours	Yellow, White, Blue
Line Widths	100 Millimeters
Roll Diameters	Up to 1.35 Meters

FieldTurf reserves the right to modify technical specifications on this product. Delivered products can vary slightly from the technical data. FieldTurf guarantees the technical quality of the proposed article.